



The Rhino Cart® Package Part No. TDQ612075-K2 includes the mobile welding table + 122 pc. fixturing kit TDK6200.

UDN6150 x4	PT09K x2	T51655 x2	UDV45M x4	T64217 x6	T64211 x4	T64216 x20
Clamp				Locate / Support		
Inserta Clamp, T-Handle 150 mm opening, 83 mm reach, 16 x 8 mm (D Rail)	Inserta Pliers, 100 mm opening, 75 mm reach	T-Post Clamp, 114 x 83 mm, T-Handle	MagSpring Clamp, 75 mm capacity, 83 mm throat depth	Magnetic V-Clamp Pad <i>*PATENTED*</i>	V-Block Spacer, Ø38 x 11.5 mm	V-Block, Ø40 x 22.6 mm
0.6 kg	0.4 kg	0.6 kg	0.5 kg	0.02 kg	0.1 kg	0.02 kg
T60210 x2	T60305 x2	T60310 x2	T60320 x5	T60330 x4	T60505 x2	T60630 x4
Stop / Support					Stop / Extend	
Econo Stop, 50 x 138 x 200 mm	Right Angle Bracket, 91 x 91 x 30 mm	Right Angle Bracket, 90 x 150 x 30 mm	Right Angle Bracket, 193 x 150 x 30 mm	Right Angle Bracket, 300 x 150 x 50 mm	Straight Edge Stop, 150 x 30 x 12 mm	Aluminum D-Stop Bar, 121.2 x 25 x 11.5 mm
1.7 kg	0.3 kg	0.4 kg	0.6 kg	2.0 kg	0.2 kg	0.04 kg
T60510 x4	T60517 x3	T65055 x42	T64201 x2	T65020 x4	T932607 x2	T65804 x2
Stop / Support		Locate / Lock				Spacer
Straight Edge Stop, 200 x 30 x 12 mm	Straight Edge Stop, 250 x 30 x 12 mm	Ball Lock Bolt, adjustable range: 22 ~ 27 mm, connecting tables to accessories, and accs. to accs.	Locating Pin goes into 16 mm holes, 33.5 mm H, no locking	Ball Lock Bolt, flush, 24 mm capacity, connecting 2 accessories	Socket Shoulder Screws Set, flush, 20 mm	Receiver Bushing, 4 mm thick, use with 24 mm Ball Lock Bolts for 28 mm combined thickness
0.3 kg	0.4 kg	0.07 kg	0.07 kg	0.05 kg	0.04 kg	0.01 kg